


CATALOG CARD

Model



NS100TRI 300m



Ø	1,00 (Cu)	4,80 (FPE)	4,90 (Al/PET)	5,50 (Al)	5,60 (Al/PET)	6,80 (PVC)
---	--------------	---------------	------------------	--------------	------------------	---------------

APPLICABLE STANDARDS

1. PN-EN 50117-2-4: 2005+A1:2008. Coaxial cables - Part 2-4: Sectional specification for cables used in cabled distribution networks - Indoor drop cables for systems operating at 5 MHz - 3 000 MHz.
2. PN-EN 50117-1:2003+A1: 2007. Coaxial cables - Part 1: Generic specification.
3. Directive 2011/65/EU with annex II 2015/863 (RoHS 3)

PRODUCT DESCRIPTION

Triple-shielded coaxial cable with inner conductor made of copper wire. The conductor is covered with physically foamed nitrogen (N) polyethylene, which has particularly effective dielectric insulation. Shielding is made in accordance with the Trishield standard, which uses triple conductor protector. The first of them is a layer of AL/PET aluminium foil, second one is aluminium wire braiding with optical coverage 90% and the last one is another layer of AL/PET aluminium foil. The outer sheath is made of white PVC, which protects against mechanical damage and allows quick and comfortable cable installation. NS100TRI cable has a high shielding efficiency, confirmed by class A. Accordance with CPR (CE) norms: EN 50575:2014, EN 13501-6:2014, Reaction to fire: ECA, Certificated by Institute of Communication.

IMPLEMENTATION

Coaxial cable enables transmission of digital and sinusoidal signals in the range 20 Hz- 15 Ghz. It is used for creating lead connections in ICT installations. The NS100TRI cable is dedicated to internal individual and multiswitch installations. It can be successfully used for receiving DVB-T (Digital Video Broadcasting - Terrestrial), FM/DAB radio and DVB-S/S2 satellite television. It is also implemented for industrial installations - CCTV.

TECHNICAL DATA

Type: RG-6
 Inner conductor: copper (CU), $\varnothing$ 1,00 $\pm$ 0,02 mm
 Dielectric: Polyethylene physically foamed with nitrogen (N), $\varnothing$ 4,80 $\pm$ 0,02 mm
 First screening: Al/PET foil, thickness 0.04 mm
 Braiding: 96 wires x 0.12mm (thick braid, 90%), AL wire
 Second screening: Al/PET foil, thickness 0.04 mm
 Outer diameter PVC: $\varnothing$ 6,8 mm, white
 Characteristic impedance: 75 $\pm$ 3 Ohm
 Flammability class: Eca
 Shielding class: A
 Working temperature: -20 C ÷ +70 C
 Laying temperature: 0 C ÷ +70 C
 Minimum bending radius [x cable diameter]: >8
 Purpose: indoors
 Compliance with standards: EN 13501-6:2014 (CPR), EN 50117 Klasa A, EN 50575:2014 (Eca), 2011/65/EU;2015/863 (RoHS 3)
 Length: 300 m
 Brand: **CONOTECH**

Novisat LLC

37b Zaporoska street
 53519 Wrocław
 Poland

tel.+4871 799 09 34
 www.novisat.pl
 mail: novisat@novisat.pl

Date

2022-01-10

CATALOG CARD

Model

NS100TRI 300m



ELECTRICAL DATA

Characteristic impedance (at frequency 200MHz)

75,6 Ohm

Unit capacity (C)

51,7 ± 2 pF/m

Wave speed reduction factor (Vf)

88 ± 1%

Dielectric permittivity efficiency

$\epsilon = 1,29$

Echo Attenuation

48 dB ± 1dB

Cable Attenuation (at frequency 200MHz)

8,6 dB/100m

Screening efficiency factor 30-1000 [Mhz]

≥ 85 dB


Screening efficiency factor 1500-2200 [Mhz]

≥ 75 dB

Table 1: NS100TRI cable attenuation in the frequency range 5-2200 MHz

Frequency [Mhz]	Measured value [db/100m]	Frequency [Mhz]	Measured value [db/100m]
5	1,9	800	18,4
50	4,8	1000	20,5
100	6,3	1200	22,7
200	8,6	1500	25,6
400	12,2	1800	28,3
500	13,8	2000	30,1
700	16,6	2200	31,9

NS100TRI



Novisat LLC
37b Zaporoska street
53519 Wroclaw
Poland

tel.+4871 799 09 34
www.novisat.pl
mail: novisat@novisat.pl

Date


2022-01-10

CATALOG CARD


Model




NS100TRI 300m




Graph 1: Waveform of the phase change as a function of frequency



Graph 2: Cable attenuation NS100TRI



Graph 3: Cable return loss NS100TRI - port 1



Graph 4: Cable return loss NS100TRI - port 2

TEST EQUIPMENT

- 1.Absorption pins, MDS 21, Rohde & Schwartz, Іл 10-5-2
- 2.Network analyzer, HP 8753 C, Hewlett-Packard, Іл 47-2-325
- 3.Array parameter meter S, HP 85046 B, Hewlett-Packard, Іл 10-7-3
- 4.Coaxial cable tester Calibration kit, HP 85036 B, Hewlett-Packard, Іл 60-019
5. 1503 C, Tektronix, Іл 74-0-33
- 6.Spectrum analyzer, MS 2601 K, Anritsu, Іл 47-2-278
- 7.Signal generator, Hewlett-Packard Іл 800-301656
- 8.Automatic meter C, E 315 A, MERATRONIC, Іл 08-3-4;
- 9.Absorption pins, MDS 22, Rohde & Schwartz, Іл 1801-1054

Novisat LLC
37b Zaporoska street
53519 Wrocław
Poland

tel.+4871 799 09 34
www.novisat.pl
mail: novisat@novisat.pl

Date
2022-01-10